

Features:

- Class D DSC
- 25 Watt transmit power
- 30 Watt PA, FOG, Bells and Whistles with listen back
- Audio tone control
- Dot matrix LCD display
- Submersible construction
- Noise canceling speaker microphone
- Large rotary knobs, and oversized display
- Second station capable with optional RAM+, RAM3 or VH-310
- Front Panel microphone can be remoted to rear panel and extended to 20 feet using MEK-4.
- Features a large alpha numeric keypad
- Bluetooth® capable headset (Optional BTK-2)



*Available in black or white

 RAM+ Remote Access Microphone
 CMP30 **RAM3**

 Shown with optional
 Bluetooth® headset

CLASS D
 DSC MARINE TRANSCEIVER
CLEARVOICE™
 NOISE REDUCTION TECHNOLOGY


Nothing takes to water like Horizon!

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Vertex Standard Co., Ltd. is under license. Other trademarks and trade names are those of their respective owners.

Features:

- Class D DSC
- 25 Watt transmit power
- 30 Watt PA, FOG, Bells and Whistles with listen back
- Audio tone control
- Dot matrix LCD display
- Submersible construction
- Noise canceling speaker microphone
- Large rotary knobs, and oversized display
- Second station capable with optional RAM+, RAM3 or VH-310
- Front Panel microphone can be remoted to rear panel and extended to 20 feet using MEK-4.
- Features a large alpha numeric keypad
- Bluetooth® capable headset (Optional BTK-2)

SPECIFICATIONS
GENERAL

Input Voltage	13.8 VDC ±20 %
Current Drain	Standby: 0.5 A
	Receive: 1.5 A
	Transmit: 5.5 A (Hi) 1.5 A (Lo)
Overall Dimensions	3.5" H x 9.1" W x 5.9" D
Flush-Mount Dimensions	2.8" H x 8.1" W x 5.1" D
Weight	3.2 lbs (1.5 kg)
PA/FOG Power Output	30 W with Listen back

TRANSMITTER

RF Output	25 W (Hi) 1 W (Lo)
Conducted Spurious Emissions	80 dB (Hi) 66 dB (Lo)
Frequency Stability	±0.0005 % (-4° F to +140° F)
FM Hum and Noise	50 dB

RECEIVER

Sensitivity	12 dB SINAD: 0.30 μV
Selectivity	-80 dB / Spurious and Image Rejection (TYP)
	-80 dB / Intermodulation and Rejection at 12 dB SINAD (TYP)
Audio Output	4.5 W
DSC Format	Class D ITU-R M493-12
NMEA In/Out	Output : DSC and DSE Input : GLL, GGA, RMC and GNS

Standard Horizon reserves the right to make changes and enhancements to products at our discretion. Current specifications are therefore subject to change without notice.

OPTIONAL ACCESSORIES

 BH-2A Bluetooth® Headset	 BTK-2 Bluetooth® Kit / BH-2A,BU-1,CAB-2	 BU-1 Bluetooth® Unit	 CAB-2 Charger unit for BH-2	 RAM3 CMP30B New remote station microphone (Black)	 RAM3 CMP30W New remote station microphone (White)
 CMP25B Remote station microphone (Black)	 CMP25W Remote station microphone (White)	 CT-100 23 ft extension cable for CMP30 or VH-310	 CVS2500 4-code voice scrambler	 MLS-300 External speaker	 MLS-310 External speaker with 10 W amplifier
 MEK-4 Microphone Extension Kit (20 ft)	 MMB-84 Flush mount bracket	 VH-310 Remote telephone style handset	 220SW 4.5" Round 4 ohm PA/Hailing horn	 240SW 5 X 8" Retangular 4 ohm PA/hailing horn	

